

Design

- Wearlayer :* 0,55 mm crosslinked PVC with PUR treatment
- Core:* 8,7 mm HDF
- Balancelayer:* 120 g paper
- Backing:* 1 mm Cork
- Clic-joint:* Rolloc 5G, fold down
- Thickness:* 11 mm



Measures

	Width	Length	Pack	Pallet
Maxwear	195 mm	1190 mm	1,86 m ² /18 kg	81,84 m ² /735 kg

Test results

Characteristic	Classification	Standard
Emission of formaldehyde	E1	EN 717-1
Fire classification	B _{fl-s1}	EN 13501-1
Wear Group	T	EN 660-2
Wear layer	0,55 mm	EN 429
Light fastness	>=6	ISO 105 B02
Stain resistance	Very Good	EN 423
Resistance to chemicals	Very good	EN 423
Level of use	23-33-42	EN 685

MaxWear is a flooring material developed by Golvabia together with Europes leading LVT producer. The result is a flooring with unique properties, suitable in both demanding domestic use and tough contract environments.

- The wear layer is made with a new patented technology which crosslinks the vinyl surface and makes it both harder and more resistant than conventional Vinyl.
- With a Vinyl surface with warm embossing, you get a comfortable, tough and nice looking floor, still easy to install with 5G-click on HDF core.
- Natural Cork backing, is used to give an integrated underlay and soundreducing properties.
- All edges have been treated with a wax based lacquer, in order to improve the moisture resistance for the wood based floor.

